




MISTA Random

DESCRIPTION: Paver TEXTURE: Multi-textured



Specifications per pallet		Imperial	Metric
A 	Product dimension (L x W x H) A	3 15⁄₁₆ × 7 7⁄₈ × 2 9⁄₁₆	100 × 200 × 65
	Product dimension (L x W x H) B	7 7⁄₈ × 7 7⁄₈ × 2 9⁄₁₆	200 × 200 × 65
	Product dimension (L x W x H) C	11 13⁄₁₆ × 7 7⁄₈ × 2 9⁄₁₆	300 × 200 × 65
80 units / pallet			
B 	Cubing	116.20 ft²	10.80 m²
100 units / pallet			
C 	Approx. Weight	3 356 lbs	1 522 kg
	Number of rows	10	
	Coverage per row	11.62 ft²	1.08 m²
90 units / pallet			
Lin. coverage per row		17.71 lin. ft	5.40 lin. m

Pallet Overview



Chestnut Brown

Multi-textured



Sandlewood

Multi-textured



Champlain Grey

Multi-textured




Shale Grey

Multi-textured




Laying Patterns Options


04 | Modular



05 | Modular



06 | Linear



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

See page 6 for icons description.

See page 27 for more information about applications.

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 100 to 105 for more technical information.

JOINT WIDTH: 3⁄₁₆" to 9⁄₁₆" (4 to 14 mm)

% OF SURFACE OPENING: 6.3 %

INFILTRATION RATE: 610 in./hr (15 505 mm/hr)

Permeable pavers allow for storm water drainage and manage excess runoff. The use of permeable pavers also facilitates LEED® certification easier to obtain.

Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.