




BLU 60 mm (6" × 13")


DESCRIPTION: Slab TEXTURE: Slate and HD² Slate



Specifications per pallet		Imperial	Metric
 198 units / pallet	Product dimension (L × W × H)	6 ½ × 13 × 2 ¾	165 × 330 × 60
	Cubing	116.05 ft²	10.78 m²
	Approx. Weight Slate	3 138 lbs	1 423 kg
	Approx. Weight HD² Slate	3 183 lbs	1 444 kg
	Number of rows	11	
	Coverage per row	10.55 ft²	0.98 m²
	Lin. coverage per row	Depth 19.5 lin. ft Length 9.75 lin. ft	5.94 lin. m 2.97 lin. m



Laying Patterns Options



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

See page 6 for icons description.
See page 26 for more information about applications.
See page 34 to 36 for more technical information. When used in a permeable pavement application, see page 100 to 110 for more technical information.

JOINT WIDTH: ⅝" (7 mm)
% OF SURFACE OPENING: 4.8%
INFILTRATION RATE: 570 in./hr (14 475 mm/hr)

*HD² Slate is only available in USA.

Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.

