




# BLU 60 mm

**DESCRIPTION:** Slab **TEXTURE:** Polished

## Pallet Overview



Polished  
Chestnut Brown




Polished  
Beige Cream



Polished  
Greyed Nickel






Polished  
Shale Grey




Polished  
Onyx Black

## Specifications per pallet


		Imperial	Metric
<b>A</b> 	Product dimension (L x W x H) <b>A</b>	6 1/2 x 13 x 2 3/16	165 x 330 x 55
	Product dimension (L x W x H) <b>B</b>	13 x 13 x 2 3/16	330 x 330 x 55
44 units / pallet	Product dimension (L x W x H) <b>C</b>	19 1/2 x 13 x 2 3/16	495 x 330 x 55
<b>B</b> 	Cubing	116.82 ft <sup>2</sup>	10.96 m <sup>2</sup>
	44 units / pallet	Approx. Weight	3 125 lbs / 1 417 kg
<b>C</b> 	Number of rows	11	
	Coverage per row	10.62 ft <sup>2</sup>	0.99 m <sup>2</sup>
	22 units / pallet	Lin. coverage per row	9.81 lin. ft / 3.02 lin. m

## Laying Patterns Options


01 | Modular



02 | Modular



03 | Linear



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

## NOTES

See page 6 for icons description.

See page 26 for more information about applications.

See page 34 to 36 for more technical information. When used in a permeable pavement application, see page 100 to 110 for more technical information.

Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.

**JOINT WIDTH:** 3/32" (7 mm)

**% OF SURFACE OPENING:** 4.5%\*

**INFILTRATION RATE:** 570 in./hr (14 475 mm/hr)

**Polished is made-to-order, minimum order of 500 sq. ft. Deposit required.**

\*For permeable application, the installation should be combined with Blu 6 x 13 in a modular pattern. A min. of 4.5% opening surface requires 75% of Blu 6 x 13 and 25% of Blu.