




ANTIKA

DESCRIPTION: Paver **TEXTURE:** Smooth

Pallet Overview*




Smooth
Chocolate Brown



Smooth
Chestnut Brown



Smooth
Shale Grey




Smooth
Onyx Black

Specifications per pallet

		Imperial	Metric
A		Product dimension (L x W x H) A Variable x 2 3/4"	Variable x 60
		Product dimension (L x W x H) B Variable x 2 3/4"	Variable x 60
B		Product dimension (L x W x H) C Variable x 2 3/4"	Variable x 60
		Product dimension (L x W x H) D Variable x 2 3/4"	Variable x 60
C		Product dimension (L x W x H) E Variable x 2 3/4"	Variable x 60
		Product dimension (L x W x H) F Variable x 2 3/4"	Variable x 60
D		Product dimension (L x W x H) G Variable x 2 3/4"	Variable x 60
E		Cubing	87 ft ² 8.10 m ²
F		Approx. Weight	2 183 lbs 990 kg
G		Number of rows	9
		Coverage per row	9.67 ft ² 0.90m ²

Laying Patterns Options

01 | Random



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

The Antika paver is perfect as a filler in a circle, around a fan design or on a winding pathway. Antika can also be used as a mosaic frame around any design.

See page 6 for icons description.

See page 27 for more information about applications.

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 100 to 105 for more technical information.

JOINT WIDTH: variable
% OF SURFACE OPENING: variable
INFILTRATION RATE: 993 in./hr (25 227 mm/hr)

*Pallet layout may vary.

Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.