




HYDRA

DESCRIPTION: Paver TEXTURE: Smooth

Pallet Overview



Specifications per pallet



96 units / pallet


	Imperial	Metric
Product dimension (L x W x H)	11 13/16 x 7 7/8 x 3 15/16	300 x 200 x 100
Cubing	62 ft ²	5.76 m ²
Approx. Weight	2 811 lbs	1 275 kg
Number of rows	8	
Coverage per row	7.75 ft ²	0.72 m ²
Lin. coverage per row	11.80 lin. ft	3.60 lin. m



Smooth Chestnut Brown
 Smooth Grey
 Smooth Greyed Nickel*
 Smooth Shale Grey
 Smooth Onyx Black

Laying Patterns Options

01 | Linear



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

See page 6 for icons description.
 See page 27 for more information about applications.
 See page 28 and 105 for more technical information.
JOINT WIDTH: 1/2" (13 mm)
% OF SURFACE OPENING: 8.3 %
INFILTRATION RATE: 605 in./hr (15 345 mm/hr)
 Please note that for barefoot walking areas (e.g. pool deck) dark-colored paving units could get very hot under the sun.
***Greyed Nickel is made-to-order, minimum order of 2,000 sq. ft. Deposit required.**

CHARACTERISTICS

- Clamp or Mechanical tool available for machine installation. Check with your local Techo-Bloc representative for more information.
- 6000 to 8000 sq. ft can be installed per day with mechanical installation and a team of 5 persons
- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.