




# INFLO

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



Specifications per pallet	Imperial	Metric
Cubing	62 ft <sup>2</sup>	5.76 m <sup>2</sup>
Approx. Weight	2 710 lbs	1 229 kg
Number of rows	8	
Coverage per row	7.75 ft <sup>2</sup>	0.72 m <sup>2</sup>
Linear coverage per row	11.80 lin. ft	3.60 lin. m



- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.

## CHARACTERISTICS

- Mechanical connection (tongue and groove system).
- 6000 to 8000 sq. ft can be installed per day with the TB100SI and a team of 5 persons.
- Maintains its interlocking properties, over time and under heavy traffic loads.

## NOTES


See page page 86 to 92 for more technical information.

**JOINT WIDTH:** 1/2" ( 13 mm)  
**% OF SURFACE OPENING:** 5.8 %  
**INFILTRATION RATE:** 837 IN./HR  
 (21 267 MM/HR)

Unit dimensions	in	mm	Units /pallet
Height	3 <sup>15</sup> / <sub>16</sub>	100	96 units
Width	7 <sup>7</sup> / <sub>8</sub>	200	
Length	11 <sup>13</sup> / <sub>16</sub>	300	



## 01 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

shale grey



chestnut brown



grey

