




INFLO

DESCRIPTION: Paver **TEXTURE:** Smooth

PALLET OVERVIEW



Specifications per pallet	Imperial	Metric
Cubing	62 ft ²	5.76 m ²
Approx. Weight	2 710 lbs	1 229 kg
Number of rows	8	
Coverage per row	7.75 ft ²	0.72 m ²
Linear coverage per row	11.80 lin. ft	3.60 lin. m

Unit dimensions	in		mm		Units/pallet
	in	mm	in	mm	
Height	3 15/16	100	3 15/16	100	96 units
Width	7 7/8	200	7 7/8	200	
Length	11 13/16	300	11 13/16	300	



- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.

CHARACTERISTICS


- Mechanical connection (tongue and groove system).
- 6000 to 8000 sq. ft can be installed per day with the TB100SI and a team of 5 persons.
- Maintains its interlocking properties, over time and under heavy traffic loads.

NOTES

See page 89 to 95 for more technical information.

JOINT WIDTH: 1/2" (13 mm)
% OF SURFACE OPENING: 5.8 %
INFILTRATION RATE: 837 IN./HR
 (21 267 MM/HR)

01 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

shale grey

chestnut brown

grey

