




NEW

HYDRA

DESCRIPTION: Paver **TEXTURE:** Smooth

PALLET OVERVIEW



- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.

CHARACTERISTICS

- Clamp or Mechanical tool available for machine installation. Check with your local Techo-Bloc representative for more information.
- 6000 to 8000 sq. ft can be installed per day with mechanical installation and a team of 5 persons

NOTES

See page 90 to 96 for more technical information.


JOINT WIDTH: 1/2" (13 mm)
% OF SURFACE OPENING: 8.3 %
INFILTRATION RATE: 837 in./hr
 (21 267 mm/hr)

Specifications per pallet	Imperial	Metric
Cubing	62 ft²	5.76 m ²
Approx. Weight	2 811 lbs	1 275 kg
Number of rows	8	
Coverage per row	7.75 ft ²	0.72 m ²
Linear coverage per row	11.80 lin. ft	3.60 lin. m



Unit dimensions	in	mm	Units/pallet
Height	3 15/16	100	96 units
Width	7 7/8	200	
Length	11 13/16	300	

01 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

Grey

Shale Grey

