




VILLAGIO

DESCRIPTION: Paver TEXTURE: Beveled

PALLET OVERVIEW



The Villagio paver allows for gentle curves and winding pathways, eliminating the need for cuts.

NOTES





See page 44 to 47 for more technical information. When used in a permeable pavement application, see page 86 to 92 for more technical information.

JOINT WIDTH: 3/8" TO 9/16" (9 TO 15 mm)


% OF SURFACE OPENING: 8.0 %

INFILTRATION RATE: 896 IN./HR (22 750 MM/HR)


Specifications per pallet	Imperial	Metric
Cubing	117 ft ²	10.88 m ²
Approx. Weight	3 029 lbs	1 374 kg
Number of rows	11	
Coverage per row	10.64 ft ²	0.99 m ²
Linear coverage per row	24.94 lin. ft	7.61 lin. m

	Unit dimensions	in	mm	Units/pallet
	Height	2 3/8	60	77 units
	Width	5 1/8	130	
	Length	5 1/8	130	
	Height	2 3/8	60	77 units
	Width	5 1/8	130	
	Length	6 5/16	160	
	Height	2 3/8	60	154 units
	Width	5 1/8	130	
	Length	7 5/16	185	
	Height	2 3/8	60	154 units
	Width	5 1/8	130	
	Length	8 7/16	215	


01 | Linear pattern




02 | Modified Herringbone pattern



03 | Modified Herringbone pattern



04 | Modified Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

